



Material Safety Data Sheet

STYRENE MONOMER - C1501

Infosafe No.: HK182

Version No.: 5.0

Issued Date: 2/03/2015

Issued by: NUPLEX COMPOSITES a
division of Nuplex Industries (Aust) Pty
Ltd (ABN 25 000 045 572)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name

STYRENE MONOMER - C1501

Product Code

C695036

Company Name

NUPLEX COMPOSITES a division of Nuplex Industries (Aust) Pty Ltd (ABN 25 000 045 572)

Address

49 - 61 Stephen Road, BOTANY NSW 2019

New Zealand: NUPLEX COMPOSITES a division of Nuplex Industries Limited, Level 3 Millennium Centre, 602C Great South Road Ellerslie 1051

NEW ZEALAND

Emergency Tel.

Australia: 1800 022 037 (24H)

New Zealand: 0800 154 666 (24H)

Telephone/Fax Number

Telephone: Australia: +61 (02) 9666 0331(BH); New Zealand: +64 (09) 583 6500(BH) Fax number: Australia: +61 (02) 9666 6661; New Zealand: +64 (09) 525 3709

Email

compliance@nuplex.com.au

Recommended Use

Industrial uses:

Manufacturing purposes (Styrene)

Continuous mass polymerisation of Polystyrene (HIPS and GPPS): Industrial

Batch suspension polymerisation of Polystyrene (HIPS and GPPS): Industrial

Production of expandable polystyrene: Industrial

Production of styrenic copolymers: Industrial

Manufacturing of UP/VE resins and formulated resins:

FRP manufacturing in an industrial setting

Production of styrene butadiene rubber (SBR): Industrial

Production of styrene butadiene latex (SBL): Industrial

Production of styrene isoprene copolymers: Industrial

Production of other styrene based polymeric dispersions:

Production of filled polyols:

Professional uses:

FRP manufacturing in a professional setting

Consumer uses:

Use of liquid UP resin for repair purposes:

Use of resin paste used as fillers/putties:

2. HAZARD IDENTIFICATION

Hazard Classification

Classified as Hazardous according to criteria of National Occupational Health and Safety Commission (NOHSC), Australia. Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Risk Phrase(s)

R10 Flammable.

R20 Harmful by inhalation.

R36/38 Irritating to eyes and skin.

R37 Irritating to respiratory system.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R65 Harmful: may cause lung damage if swallowed.

Safety Phrase(s)

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe gas/fumes/vapour/spray

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37 Wear suitable protective clothing and gloves.

S46 If swallowed, seek medical advice immediately and show this container or label.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization

Liquid

Ingredients

Name	CAS	Proportion
Styrene	100- 42- 5	100 %

Preparation Description

Styrene and stabiliser: 4-tert-Butylpyrocatechol (CAS 98-29-3)

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Do not induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (131 126)

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray, carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon monoxide and carbon dioxide.

Specific Hazards

Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

3Y

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

Unsuitable Extinguishing Media

Do not use water jet.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with local exhaust ventilation, away from sparks, flames and other ignition sources. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers tightly closed. Take precautionary measures against static discharges. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Conditions for Safe Storage

Store in the shade, in a well-ventilated area preferably below 40°C and well away from sources of ignition. This product should be stored away from foodstuffs, strong oxidising agents and other incompatible materials. Handle and store in accordance with applicable local and national regulations for flammable liquids. The product has a limited storage life due to inhibitor depletion and should be used within six months of delivery. Rapid polymerisation resulting in violent rupture of closed containers and possible fire from flammable vapours may be initiated by high temperatures or certain contaminants. Oxidising agents (e.g. organic peroxides), strong acids (e.g. sulphuric acid), ferrous salts present in rust, and some metal halides promote polymerisation. Alkalis reduce the inhibitor concentration and increase the risk of spontaneous polymerisation. Contamination of the product with these substances should be avoided. Exposure to UV radiation (including from light fittings), can initiate slow polymerisation that may continue in a sealed container. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local and national regulations.

Storage Temperatures

This product should not be stored at temperatures above 40°C.

Unsuitable Materials

Brass, copper, copper alloys

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards

Substance	Regulations	Exposure Duration	Exposure Limit	Units	Notes
Styrene	Safe Work Australia	TWA	50	ppm	
Styrene	Safe Work Australia	TWA	213	mg/m3	
Styrene	Safe Work Australia	STEL	100	ppm	
Styrene	Safe Work Australia	STEL	426	mg/m3	

Biological Limit Values

Name: Styrene [100-42-5]

Determinant: Mandelic acid plus phenylglyoxylic acid in urine

BEI®: 400mg/g creatinine

Sampling time: End of shift.

Determinant: Styrene in venous blood

BEI®: 0.2mg/l

Sampling time: End of shift.

Source: American Conference of Industrial Hygienists (ACGIH)

Engineering Controls

Provide sufficient ventilation to keep airborne levels below the exposure limits or as low as possible. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Liquid

Appearance

Colourless to yellowish liquid

Odour

Characteristic

Decomposition Temperature

Not available

Melting Point

-31°C

Boiling Point

145.2°C

Solubility in Water

320mg/l (25°C)

pH Value

Not available

Vapour Pressure

6.67 hPa (20°C) (styrene)

Vapour Density (Air=1)

Not available

Evaporation Rate

Not available

Odour Threshold

Not available

Viscosity

Refer to Section 9: Kinematic Viscosity and Dynamic Viscosity

Colour

Colourless to yellowish

Volatile Component

Not available

Octanol/Water Partition Coefficient

log Pow: 2.96 (25°C)

Density

0.9-0.91g/cm³ (20°C)

Flash Point

31°C

Flammability

Flammable liquid.

Auto-Ignition Temperature

490°C

Flammable Limits - Lower

Not available

Flammable Limits - Upper

Not available

Explosion Properties

Not available

Oxidising Properties

Not available

Kinematic Viscosity

Not available

Dynamic Viscosity

0.696mPas (25°C)

10. STABILITY AND REACTIVITY

Stability and reactivity

Refer to Section 10: Possibility of hazardous reactions

Chemical Stability

Stable under normal conditions of storage and handling.

Conditions to Avoid

Heat, open flames and other sources of ignition.

Incompatible materials

Alkylation catalysts and strong acids (H₂SO₄, H₃PO₄, BF₃, AlCl₃), halogens and hydrogen halides. Contact with copper and copper alloys. Oxidising agents, strong acids.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes including: carbon monoxide and carbon dioxide.

Hazardous Reactions

Reacts with incompatible materials. May react with oxygen to form peroxides.

Hazardous Polymerization

May occur in the presence of polymerisation accelerators.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

Available toxicity data is given below.

Inhalation

Harmful by inhalation. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system. Irritating to respiratory system. Inhalation of product vapours will cause irritation of the nose, throat and respiratory system.

Ingestion

Harmful: may cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause pulmonary injury. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

Skin

Irritating to skin. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Result: Irritating (rabbit)

Corporate Social Responsibility Report

Eye

Irritating to eyes. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Result: Irritating (rabbit)

Corporate Social Responsibility Report

Chronic Effects

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Inhalation can cause irritation of the nose, throat and respiratory system. Long-term exposure to styrene may cause peripheral neuropathy, CNS depression, and damage to the liver and kidneys.

Mutagenicity

Result: no indication of mutagenic effects

Corporate Social Responsibility Report

Carcinogenicity

Styrene is listed as a Group 2B: Possibly carcinogenic to humans according to International Agency for Research on Cancer (IARC).

Acute Toxicity - Oral

Styrene

LD50 (rat): 5000 mg/kg

Corporate Social Responsibility Report

Acute Toxicity - Dermal

Styrene

LD50 (rat): >2000 mg/kg

Corporate Social Responsibility Report

Acute Toxicity - Inhalation

Styrene:

LC50 (rat): 11.8mg/l/4h

Corporate Social Responsibility Report

Skin Sensitisation

Non-sensitizing (Human Effects)

Corporate Social Responsibility Report

12. ECOLOGICAL INFORMATION

Ecotoxicity

The available ecological data is given below.

Persistence / Degradability

Biodegradable (Corporate Social Responsibility Report)

Mobility

Not available

Bioaccumulative Potential

Styrene

Not expected to be bioaccumulative

logPow 2.96 (25°C)

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

Acute Toxicity - Fish

Styrene

LC50 (Pimephales promelas): 4.02mg/l/96h

Corporate Social Responsibility Report

Acute Toxicity - Daphnia

Styrene

EC50 (Daphnia magna): 4.7mg/l/48h

Corporate Social Responsibility Report

Acute Toxicity - Algae

Styrene

EC50 (Pseudokirchneriella subcapitata): 4.9mg/l/72h

Corporate Social Responsibility Report

Acute Toxicity - Bacteria

Styrene

EC50 (activated sludge): 500mg/l/30min

Corporate Social Responsibility Report

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near containers. Empty containers may contain flammable residues. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Advise flammable nature. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Controlled incineration is recommended.

14. TRANSPORT INFORMATION

Transport Information

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:

Class 1: Explosives

Division 2.1: Flammable gases (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L)

Division 2.3: Toxic gases

Division 4.2: Spontaneously combustible substances

Division 5.1: Oxidising substances and Division 5.2: Organic peroxides

Class 6: Toxic or Infectious Substances (where the flammable liquid is nitromethane)

Class 7: Radioactive materials unless specifically exempted

U.N. Number

2055

Proper Shipping Name

STYRENE MONOMER, STABILIZED

DG Class

3

Packing Group

III

Hazchem Code

3Y

IERG Number

19P

UN Number (Air Transport, ICAO)

2055

IATA/ICAO Proper Shipping Name

STYRENE MONOMER, STABILIZED

IATA/ICAO Hazard Class

3

IATA/ICAO Packing Group

III

IATA/ICAO Symbol

Flammable Liquid

IMDG UN No

2055

IMDG Proper Shipping Name

STYRENE MONOMER, STABILIZED

IMDG Hazard Class

3

IMDG Pack. Group

III

IMDG Marine pollutant

No

IMDG EMS

F-E,S-D

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to criteria of National Occupational Health and Safety Commission (NOHSC), Australia.
Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule

S5

16. OTHER INFORMATION

Date of preparation or last revision of MSDS

SDS Reviewed: March 2015, Supersedes: February 2015

Contact Person/Point

IMPORTANT ADVICE: This MSDS summarizes our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact the supplier listed in section 1 of the SDS. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

NUPLEX MSDS WARNING: Nuplex Group (Nuplex) is aware that third parties are distributing documents purporting to be MSDSs (or the like) in relation to Nuplex products without any authorisation from Nuplex (Unauthorised MSDS). Nuplex accepts no responsibility for the distribution of an Unauthorised MSDS by a third party. All Nuplex products must be used in accordance with the corresponding original MSDS authorised by Nuplex for use with that Nuplex product (Authorised MSDS). In the event a Nuplex product is used without the Authorised MSDS and/or with an Unauthorised MSDS, Nuplex hereby excludes absolutely and to the maximum extent permitted by law all liability whatsoever and howsoever arising for all loss and/or damage including but not limited to for personal injury, sickness and death, damage to real property and chattels and direct and indirect consequential loss and loss of profits.

References

Standard for the Uniform Scheduling of Medicines and Poisons.

Approved criteria for classifying hazardous substances [NOHSC:1008(2004)].

National Code of Practice for the Preparation of Material Safety Data Sheets [NOHSC:2011(2003)].

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe work Australia.

American Conference of Industrial Hygienists (ACGIH)

Technical Contact Numbers

For further information ask for: For specialist advice in emergencies: 1800 022 037

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.