

		<p>3281 Guasti Road, Suite 260          Ontario, CA 91761          (909) 987-0550 (800) 538-3091          Fax: (909) 987-0490</p> <hr/> <p><b>PRODUCT SALES SHEET: Z-Poxy 30 Min System</b></p>
---	---	---

Pacer Technology's Hobby product Z-Epoxy 30 Min System (PT39) works for installing firewalls and bulkhead in fiberglass fuselages and boat hulls.

**PROPERTIES**

Initial color: Clear hazy to light yellow

Final color: Light yellow

Set Time: 30 minutes @ 65-80F

Handling Time: After 7 hours

Full Strength: 24 hours

Maximum Gap: .25"

Hardness, Shore D: 75-83 (After full cure)

Shear Strength, Steel: 2500 psi (± 20%)

Aluminum: 1400 psi (± 20%)

Operating Temperature Range: -65°F to +225°F  
 (-54°C to +107°C)

**USE INSTRUCTIONS**

1. Surfaces should be clean and dry, free from oil and grease.
2. Roughen surfaces with emery cloth or sandpaper for best results.
3. Refer to opening instructions on card. Dispense equal amounts from both bottles and mix thoroughly, approximately 1 minute.
4. Apply to both surfaces and mate parts together.
5. Remove excess epoxy immediately with denatured alcohol.
6. Sets in 30 minutes at room temperature (77F or 25C) with full cure in 24 hours. Note – For cooler temperatures, setting time may be longer. Product can also be heat cured at 200F for 35-45 minutes for full cure properties.

**STORAGE AND SHELF LIFE**

After use, wipe tips to remove residual product and reseal with plug. Store product sealed, with tips up, in a cool, dry location. Stored under these conditions, a one-year shelf life can be expected.

**SAFETY AND HANDLING PRECAUTIONS**

Contains Epoxy resin & Mercaptan hardener. May cause eye/skin irritation with direct contact. In case of direct eye contact, flush with water for 15 minutes and consult physician. Wash hands and skin thoroughly with soap and water after use. If swallowed, seek medical advice immediately and show container label. Keep out of reach of children.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ [www.supergluecorp.com](http://www.supergluecorp.com) and click on the ZAP logo. In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or call (909) 987-0550.

2015 – rev 2 mkr

The data contained herein is furnished for descriptive purposes only and is believed to be reliable. Users of any products described in the data sheet have the responsibility to determine the suitability for their particular use thereof, and Pacer relies upon such users to adopt all necessary precautions to ensure the protection of property and persons against hazards involved in the use thereof.

Pacer Technology specifically makes no warranty, representation, or condition of any nature, kind or character, whether express or implied, including, but not limited to, warranties or merchantability or fitness for a particular purpose arising from the sales or use of products described in this data sheet, and none shall be implied by law. Pacer Technology specifically disclaims any liability for consequential or incidental damage of any kind, including lost profit.