

1. IDENTIFICATION

Product Name: Black Raspberry Fragrance
Other Names:
Product Use Description: Fragrance for Consumer Product.

Contact Information:

Organisation	Location	Telephone	Ask For
Adelaide Moulding and Candle Supplies	7 Woodlands Terrace Edwardstown, South Australia, 5039	08 8294 0451	SDS Officer
Poisons Information Centre		13 11 26	

2. HAZARD IDENTIFICATION

Classification of Substance of Mixture: Flammable Liquids (Category 4)
 Skin Corrosion/Irritation (Category 2)
 Eye Damage / Irritation (Category 2)
 Sensitization - Skin (Category 1)
 Hazardous to the Aquatic Environment - Acute Hazard (Category 1)
 Hazardous to the Aquatic Environment - Long-term Hazard (Category 1)
 H227, Combustible liquid.
 H315, Causes skin irritation.
 H317, may cause an allergic skin reaction.
 H319, Causes serious eye irritation.
 H410, very toxic to aquatic life with long lasting effects.

Hazard Pictogram(s):



Signal Word: WARNING

Hazard Statements (s): H227 Combustible liquid.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319, Causes serious eye irritation.
 H410, Very toxic to aquatic life with long lasting effects.

Precautionary Statements(s): P210, Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.
 P261, Avoid breathing vapour or dust.
 P264, Wash hands and other contacted skin thoroughly after handling.
 P272, Contaminated work clothing should not be allowed out of the workplace.
 P273, Avoid release to the environment.
 P280, Wear protective gloves/eye protection/face protection.
 P302/352, IF ON SKIN: Wash with plenty of soap and water.
 P305/351/338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333/313, If skin irritation or rash occurs: Get medical advice/attention.
 P337/313, If eye irritation persists: Get medical advice/attention.
 P362, Take off contaminated clothing and wash before reuse.
 P370/378, In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
 P391, Collect spillage.
 P403/235, Store in a well-ventilated place. Keep cool.
 P501, dispose of contents/container to approved disposal site, in accordance with local regulations.

Other Hazards: None

3. INFORMATION ON INGREDIENTS

Mixtures:

EC No.	CAS No.	Description	GHS Classification	%
214-946-9	1222-05-5	1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran	Skin Irrit. 3-Aquatic Acute 1-Aquatic Chronic 1;H316-H410	50-100%
204-116-4	115-95-7	Linalyl acetate	Flam. Liq. 4-Skin Irrit. 2-Eye Irrit. 2AAquatic Acute 3;H227-H315-H319-H402	10-<20%
227-813-5	5989-27-5	Limonene	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1BAsp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H226-H304-H315-H317-H410	5-<10%
201-134-4	78-70-6	Linalool	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 3; H227-H303-H315-H317-H319-H402	5-<10%
201-061-8	77-83-8	Ethyl methylphenylglycidate	Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2;H317-H411	5-<10%
201-550-6	84-66-2	Diethyl phthalate	Skin Irrit. 3-Aquatic Acute 3;H316-H402	1-<5%
203-347-8	105-95-3	Ethylene brassylate	Aquatic Acute 2;H401	1-<5%
260-709-8	57378-68-4	delta-1-(2,6,6-Trimethyl-3-cyclohexen-1-yl)-2-buten-1-one	Acute Tox. 4-Skin Irrit. 2-Skin Sens. 1AAquatic Acute 1-Aquatic Chronic 1;H302- H315-H317-H410	1-<5%
203-745-1	110-19-0	Isobutyl acetate	Flam. Liq. 2-STOT SE 3-Aquatic Acute 3; H225-H336-H402	1-<5%
226-806-4	5471-51-2	4-(p-Hydroxyphenyl)-2-butanone	Aquatic Acute 3;H402	1-<5%
211-892-8	706-14-9	gamma-Decalactone	Skin Irrit. 3;H316	1-<5%
204-881-4	128-37-0	Butylated hydroxytoluene	Aquatic Acute 1-Aquatic Chronic 1;H410	1-<5%
225-582-5	4940-11-8	Ethyl maltol	Acute Tox. 4;H302	1-<5%
226-394-6	5392-40-5	Citral	Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2Askin Sens. 1B-Aquatic Acute 2;H313- H315-H317-H319-H401	0.1-<1%
202-680-6	98-55-5	alpha-Terpineol	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Aquatic Acute 2;H227-H303-H315-H319-H401	0.1-<1%
204-872-5	127-91-3	beta-Pinene	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1BAsp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H226-H304-H315-H317-H410	0.1-<1%
203-377-1	106-24-1	Geraniol	Acute Tox. 5-Skin Irrit. 2-Eye Dam. 1- Skin Sens. 1-Aquatic Acute 3;H303- H315-H317-H318-H402	0.1-<1%
203-093-8	103-26-4	Methyl cinnamate	Acute Tox. 5-Skin Sens. 1B;H303-H317	0.1-<1%
242-362-4	18479-58-8	Dimyrcetol	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Aquatic	0.1-<1%

			Acute 3;H227-H303- H315-H319-H402	
207-431-5	470-82-6	Eucalyptol	Flam. Liq. 3-Acute Tox. 5-Skin Irrit. 3- Skin Sens. 1B;H226-H303-H316-H317	0.1-<1%
204-622-5	123-35-3	Myrcene	Flam. Liq. 3-Skin Irrit. 2-Eye Irrit. 2A-Asp. Tox 1;H226-H304-H315-H319	0.1-<1%

Substances with Community workplace exposure limits, not listed above

EC No.	CAS No.	Description	%
204-881-4	128-37-0	Butylated hydroxytoluene	1.00%
201-550-6	84-66-2	Diethyl phthalate	2.93%
203-745-1	110-19-0	Isobutyl acetate	1.65%

4. FIRST AID MEASURES

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin Contact: Wash with plenty of soap and water.

Most Important Symptoms Acute and Delayed: Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

Indications of Immediate Medical Attention and Special Treatment Needed: None

5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Use foam, carbon dioxide or dry chemical.

Hazardous Combustion Products: In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

Advice for Fire Fighters: In case of insufficient ventilation, wear suitable respiratory equipment.

6. ACCIDENTAL RELEASE MEASURES

Protective Equipment, Personal Precautions and Emergency Procedures: Avoid inhalation. Avoid contact with skin and eyes.
See protective measures under Section 7 and 8.

Environmental Precautions: Keep away from drains, surface and ground water, and soil.

Methods and Suitable materials for containment and cleaning up: Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

7. HANDLING AND STORAGE

Safe Handling: Keep away from heat, sparks, open flames, and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation Do not eat, drink, or smoke when using this product.

Safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. To prevent congealing and denaturing it is recommended that goods are stored at temperatures between 15 - 30°C. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Workplace exposure limits:**

Ingredient	CAS	EC	Description	ppm	mg/m3	Reference
Butylated hydroxytoluene	128-37-0	204-881-4	Long-term exposure limit (8-hour TWA reference period)	-	-	-
			Short-term exposure limit (15-minute reference period)	-	-	-
Diethyl phthalate	84-66-2	201-550-6	Long-term exposure limit (8-hour TWA reference period)	-	-	-
			Short-term exposure limit (15-minute reference period)	-	-	-
Isobutyl acetate	110-19-0	203-745-1	Long-term exposure limit (8-hour TWA reference period)	-	-	-
			Short-term exposure limit (15-minute reference period)	-	-	-

Exposure Controls**Eye / Skin Protection:**

Wear protective gloves/eye protection/face protection

Respiratory Protection:

Ensure adequate and ongoing ventilation is maintained in order to prevent build up of excessive vapour and to ensure occupational exposure limits are adhered to. If appropriate, and depending on your patterns and volumes of use, the following engineering controls may be required as additional protective measures: a) Isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under negative air pressure relative to the rest of the plant. b) Employ the use of Personal protective equipment - an approved, properly fitted respirator with organic vapour cartridges or canisters and particulate filters. c) Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures. d) Use closed systems for transferring and processing this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colourless - Faint Yellow
Aroma/Odour:	Fruity, Berry, Vanilla
pH:	Not determined
Initial boiling point/range:	Not determined
Flash Point (closed cup test):	65 °C
Vapour pressure:	Not determined
Solubility(ies):	Not determined
Relative density:	0.9852 - 0.9992
Other information:	None available

10. STABILITY AND REACTIVITY**Reactivity Hazards:**

Presents no significant reactivity hazard, by itself or in contact with water.

Chemical Stability:

Good stability under normal storage conditions.

Hazardous Reactions:

Not expected under normal conditions of use.

Conditions to Avoid: Avoid extreme heat.

Incompatibles: Avoid contact with strong acids, alkalis, or oxidising agents.

Hazardous Decomposition Products: Not expected.

11. TOXICOLOGICAL INFORMATION

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in the UN GHS.

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

Assumed Toxicity Value (LD50 or ATE) for Acute Oral Toxicity: >5000
Assumed Toxicity Value (LD50 or ATE) for Acute Dermal Toxicity: Not Applicable
Assumed Toxicity Value (LC50 or ATE) for Acute Inhalation Toxicity: Not Available
Inhalation Route: Not Available

Information about hazardous Ingredients in the Mixture:

EC	CAS	Ingredients	LD50/ATE Oral	LD50/ATE Dermal	LC50/ATE Inhalation	LC50 Route
225-582-5	4940-11-8	Ethyl maltol	1200	Not available	Not available	Not available
260-709-8	57378-68-4	delta-1-(2,6,6-Trimethyl-3-cyclohexen-1-yl)-2-buten-1-one	1400	Not available	Not available	Not available

12. ECOLOGICAL INFORMATION

Toxicity: Very toxic to aquatic life with long lasting effects.

Persistence and degradability: Not available.

Bioaccumulative potential: Not available.

Mobility in soil: Not available.

PBT and vPvB Assessment: This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

Other Adverse Effects: Not available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods: Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

UN Number: 3082

UN Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2- benzopyran, Limonene)

Transport Hazard Class(es): 9

Sub Risk: None

Packing Group: III

Environmental Hazards: This is an environmentally hazardous substance.

Special Precautions for user: None additional

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not Applicable

15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations Specific for the substance or mixture

Water Hazard Class (WGK) 3

Chemical Safety Assessment A Chemical Safety Assessment has not been carried out for this product.

16. OTHER INFORMATION

Concentration % Limits: EH A1=40.65% EH A2=4.02% EH A3=0.40014860% EH C1=40.65% EH C2=4.03% EH C3=0.40325182% EH C4=37.60% SCI 2=36.92% SCI 3=2.87% EDI 2A=47.62% SS 1=6.06%

Total Fractional Values: EH A1=2.46 EH A2=24.90 EH A3=249.91 EH C1=2.46 EH C2=24.80 EH C3=247.98 EH C4=2.66 SCI 2=2.71 SCI 3=34.79 EDI 2A=2.10 SS 1=16.50

Key to revisions: Not applicable

Key to abbreviations:

Abbreviation	Meaning
Acute Tox. 4	Acute Toxicity - Oral Category 4
Acute Tox. 5	Acute Toxicity - Oral Category 5
Acute Tox. 5	Acute Toxicity - Dermal Category 5
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Asp. Tox 1	Aspiration Hazard Category 1
Eye Dam. 1	Eye Damage / Irritation Category 1
Eye Irrit. 2A	Eye Damage / Irritation Category 2A
Flam. Liq. 2	Flammable Liquid, Hazard Category 2
Flam. Liq. 3	Flammable Liquid, Hazard Category 3
Flam. Liq. 4	Flammable Liquid, Hazard Category 4
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
P210	Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304/340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/233/235	Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
STOT SE 3	Specific Target Organ Toxicity (Single Exposure) Category 3
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Irrit. 3	Skin Corrosion / Irritation Category 3
Skin Sens. 1	Sensitization - Skin Category 1
Skin Sens. 1A	Sensitization - Skin Category 1A
Skin Sens. 1B	Sensitization - Skin Category 1B

Further Information

The information in this safety data sheet is to the best of our knowledge true and accurate, but all data, instructions, and recommendations and/or suggestions are made without guarantee.

The Material Safety Data Sheet is intended to provide information for a health and safety assessment of the material. This document is not intended for quality assurance purposes.