

Safety Data Sheet **Crushed Candy Cane** Revision 1, Date 22/10/2020

Ask For

SDS Officer

Phone: +61 8 8294 0451

ABN: 85 765 232 986

Email: admin@amcsupplies.com.au

Web: www.amcsupplies.com.au

Regulation 330 Schedule 7 as per Safe Work SA WHS Regulations

1. IDENTIFICATION

Product Name: Crushed Candy Cane Fragrance

Other Names:

Product Use Description:

Fragrance for Consumer Product.

Contact Information: Organisation Location Telephone

> Adelaide Moulding 7 Woodlands Terrace 08 8294 0451 and Candle Supplies **Edwardstown South**

Australia 5039

Poisons Information 13 11 26

Centre

2. HAZARD IDENTIFICATION

Classification of Substance of Mixture:

Flammable Liquids (Category 4) Skin Corrosion/Irritation (Category 2) Eye Damage/Irritation (Category 2) Skin-Sensitisation (Category 1)

Hazardous to the Aquatic Environment Acute (Category 3) Hazardous to the Aquatic Environment Chronic (Category 3)

H227 Combustible Liquid. H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Hazard Pictogram(s):



Signal Word: WARNING

Hazard Statements (s): H227 Combustible liquid.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements(s): P210 Keep away from heat, sparks, open flames and hot surfaces - no smoking.

P261 Avoid breathing vapour or dust.

P264 Wash hands and other contacted skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + 352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333 + P313 If skin irritation persists: Get medical advice/attention. P337 + P313 if eye irritation persists: Get medical advice/attention

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use carbon dioxide, dry chemical, foam for extinction.

P403 + P235 Store in a well-ventilated place. Keep cool.

 $P501\ Dispose\ of\ contents/container\ to\ an\ approved\ waste\ disposal\ plant,\ in\ accordance\ with\ local\ regulations.$

3. Composition/Information on Ingredients

Mixtures:

EC No CAS No Description		Description	GHS Classification	Concentration	
201-550-6	84-66-2	Diethyl phthalate Skin Irrit. 3-Aquatic Acute 3;H31 H402		50-100%	
233-944-9	10458-14-7	Menthone	nthone Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2- Skin Sens. 1B-Aquatic Acute 3;H227- H303-H315-H317-H402		
229-352-5	6485-40-1	I-Carvone Flam. Liq. 4-Acute Tox. 5-Skin Sens. 1BAquatic Acute 2;H227-H313-H317-H401		5-<10%	
218-690-9	2216-51-5	I-Menthol	Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2AAquatic Acute 3;H303-H315-H319-H402	1-<5%	
204-465-2	121-33-5	Vanillin	Acute Tox. 5-Eye Irrit. 2A-Aquatic Acute 3;H303-H319-H402	1-<5%	
225-582-5	4940-11-8	Ethyl maltol	Acute Tox. 4;H302	1-<5%	
204-464-7	121-32-4	Ethyl vanillin	Acute Tox. 5-Eye Irrit. 2B-Aquatic Acute 3;H303-H320-H402	1-<5%	
250-954-9	32210-23-4	4-tert-Butylcyclohexyl acetate			
207-727-4	491-07-6	d,I-Isomenthone	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2- Skin Sens. 1B-Aquatic Acute 3;H227- H303-H315-H317-H402	1-<5%	
203-377-1	106-24-1	Geraniol	Acute Tox. 5-Skin Irrit. 2-Eye Dam. 1- Skin Sens. 1-Aquatic Acute 3;H303- H315-H317-H318-H402	1-<5%	
226-806-4	5471-51-2	4-(p-Hydroxyphenyl)-2- butanone	Aquatic Acute 3;H402	1-<5%	
201-942-7	89-81-6	Piperitone	Acute Tox. 5-Skin Irrit. 3-Aquatic Acute 3; H303-H316-H402	1-<5%	
204-881-4	128-37-0	Butylated hydroxytoluene	Aquatic Acute 1-Aquatic Chronic 1;H410	0.1-<1%	
203-354-6	106-02-5	omega-Pentadecalactone Skin Irrit. 3-Skin Sens. 1B-Aquatic Chronic 2;H316-H317-H411		0.1-<1%	
207-431-5	470-82-6	Eucalyptol	Flam. Liq. 3-Acute Tox. 5-Skin Irrit. 3- Skin Sens. 1B;H226-H303-H316- H317	0.1-<1%	
202-680-6	98-55-5	alpha-Terpineol	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Aquatic Acute 2;H227- H303- H315-H319-H401	0.1-<1%	
203-375-0	106-22-9	Citronellol	Acute Tox. 5-Acute Tox. 5-Skin Irrit. 2-	0.1-<1%	

Phone: +61 8 8294 0451

ABN: 85 765 232 986

Email: admin@amcsupplies.com.au

Web: www.amcsupplies.com.au

			Eye Irrit. 2A-Skin Sens. 1B- Aquatic Acute 2;H303-H313-H315-H317-H319- H401	
201-134-4	78-70-6	Linalool	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 3; H227-H303-H315-H317-H319- H402	0.1-<1%
203-234-3	104-76-7	2-Ethyl-1-hexanol	Flam. Liq. 4-Acute Tox. 5-Acute Tox. 4- Skin Irrit. 2-Eye Irrit. 2A-STOT SE 3- Aquatic Acute 3;H227-H303- H315-H319- H332-H335-H402	0.1-<1%
204-409-7	120-57-0	Piperonal	Acute Tox. 5-Skin Sens. 1B- Aquatic Acute 2;H303-H317-H401	0.1-<1%
200-580-7	64-19-7	Acetic acid	Flam. Liq. 3-Acute Tox. 5-Acute Tox. 4- Skin Corr. 1A-Eye Dam. 1;H226- H303- H312-H314	0.1-<1%

Substances with Community workplace exposure limits, not listed above:

Name	CAS	EC	%
Butylated hydroxytoluene	128-37-0	204-881-4	0.75%
Diethyl phthalate	84-66-2	201-550-6	56.88%
Ethyl acetate	141-78-6	205-500-4	0.15%
Isobutyl acetate	110-19-0	203-745-1	0.18%

4. First Aid Measures

Skin Contact: IF ON SKIN: Wash with plenty of soap and water.

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Most important symptoms and

Causes serious eye irritation. effects both acute and delayed: Causes skin irritation.

May cause an allergic skin reaction.

Indication of any immediate Medical attention and special

treatment needed:

None expected.

5. Fire Fighting Measures

Suitable extinguishing media: Carbon dioxide, Dry chemical, foam.

Hazardous Combustion Products: In case of fire, the following can released: Carbon monoxide, Unidentified organic compounds.

Advice for Fire Fighters: In case of insufficient ventilation, wear suitable respiratory equipment.

6. Accidental Release Measures

Protective Equipment: Avoid inhalation.

Adelaide Moulding and Candle Supplies 7 Woodlands Terrace Edwardstown SA 5039 Revision 1 Page 3 of 6

Phone: +61 8 8294 0451 Email: admin@amcsupplies.com.au Web: www.amcsupplies.com.au ABN: 85 765 232 986 Avoid contact with skin and eyes.

Handle the product using protective gloves.

Remove all ignition sources and ventilate area. Personal Precautions:

Avoid contact with skin and inhalation of its vapours or smoke.

Emergency Procedures: No specific advice other than above.

Environmental Precautions: Keep away from drains, surface and ground water, and soil.

Methods and Suitable materials Remove ignition sources. for spill containment:

Provide adequate ventilation.

Avoid excessive inhalation of vapours.

Contain spillage immediately by use of sand or inert powder.

Dispose of according to local regulations.

7. Handling and Storage

Handling

Precautions for safe handling: Keep away from heat, sparks, open flames and hot surfaces.

No smoking.

Use personal protective equipment as required.

Follow good manufacturing practices for housekeeping and personal hygiene.

Use in areas with adequate ventilation.

Do not eat, drink or smoke when using this product.

Contaminated clothing and shouse should be thoroughly cleaned before reuse. Use in accordance with good manufacturing and industrial hygiene practices.

Storage

Technical measures and storage

Keep container closed when not in use.

conditions:

Store in a cool, dry, ventilated area away from sources of heat, moisture, and incompatible

Phone: +61 8 8294 0451

ABN: 85 765 232 986

Email: admin@amcsupplies.com.au

Web: www.amcsupplies.com.au

Ground/bond container and receiving equipment.

Use explosion-proof electrical, ventilating and lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static charge.

8. Exposure Controls/Personal Protection

Not Applicable Workplace exposure limits:

Ingredient	CAS	EC	Description	ppm	mg/m3	Reference
Butylated	128-37-0	204-881-4	Long-term exposure limit (8-hour TWA	-	-	-
hydroxytoluene			reference period)			
			Short-term exposure limit (15-minute	-	-	-
			reference period)			
Diethyl phthalate	84-66-2	201-550-6	Long-term exposure limit (8-hour TWA	-	-	-
			reference period)			
			Short-term exposure limit (15-minute	-	-	-
			reference period)			
Ethyl acetate	141-78-6	205-500-4	Long-term exposure limit (8-hour TWA	-	-	-
			reference period)			
			Short-term exposure limit (15-Minute	-	-	-
			reference period)			
Isobutyl acetate	110-19-0	203-745-1	Long-term exposure limit (8-hour TWA	-	-	-
			reference period)			

	Short-term exposure limit (15-minute		-	-	-
		reference period)			

Exposure Controls

Eye / Skin Protection Avoid skin contact. Wear protective gloves/eye protection/face protection

Respiratory Protection

Ensure adequate and ongoing ventilation is maintained in order to prevent build-up of excessive vapour

and to ensure occupational exposure limits are adhered to.

If appropriate, and depending on your patterns and volumes of use, the following engineering controls may be required as additional protective measures:

a) Isolate mixing rooms and other areas where this material is used or openly handled. Maintain these

areas under negative air pressure relative to the rest of the plant.

b) Employ the use of Personal protective equipment - an approved, properly fitted respirator with

organic vapour cartridges or canisters and particulate filters.

c) Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures.

d) Use closed systems for transferring and processing this material.

9. Physical and Chemical Properties

Appearance: Liquid Colour: Yellow

Aroma/Odour: Peppermint, Vanilla, Eucalyptus, Mint

Relative density: 1.0459 − 1.0599

Flash Point (closed cup test): = 90.0 °C

pH: Not determined

Initial boiling point/range: Not determined

Vapour pressure: Not determined

10. Stability and Reactivity

Reactivity Hazards: No significant reactivity hazard, by itself or in contact with water.

Chemical Stability: Stable under ordinary conditions of use and storage.

Not determined

Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Conditions to Avoid: Avoid extreme heat.

Incompatibles: Avoid contact with strong acids, alkalis, or oxidising agents.

Hazardous Decomposition

Products:

Solubility(ies):

Not expected.

11. Toxicological Information

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in the UN GHS.

Causes skin irritation.

May cause and allergic reaction. Causes serious eye irritation.

Assumed Toxicity Value (LD50 or ATE) for Acute Oral Toxicity: >5000
Assumed Toxicity Value (LD50 of ATE) for Acute Dermal Toxicity: >5000
Assumed Toxicity Value (LC50 or ATE) for Acute Inhalation Toxicity: Not Available

Inhalation Route: Not Available

Adelaide Moulding and Candle Supplies 7 Woodlands Terrace Edwardstown SA 5039 Revision 1 Page 5 of 6 Phone: +61 8 8294 0451
Email: admin@amcsupplies.com.au
Web: www.amcsupplies.com.au
ABN: 85 765 232 986

Information about hazardous Ingredients in the Mixture:

Ingredient	CAS	EC	LD50/ATE Oral	LD50/ATE	LC50/ATE	LC50 Route
				Dermal	Inhalation	
Ethyl maltol	4940-11-8	225-582-5	1200	Not available	Not available	Not available

12. Ecological Information

Toxicity: Harmful to aquatic life with long lasting effects.

Persistence and degradability: Not Available

Bioaccumulative potential: Not Available

Mobility in soil: Not Available

PBT and vPvB Assessment: This substance does not meet the PBT/vPVB criteria of REACH, annex XIII

Other Adverse Effects: Not Available

13. Disposal Considerations

Disposal: Dispose of according to local regulations.

Avoid disposing into drainage systems and into the environment.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Phone: +61 8 8294 0451

ABN: 85 765 232 986

Email: admin@amcsupplies.com.au

Web: www.amcsupplies.com.au

14. Transport Information

UN Number: Not classified

UN Proper Shipping Name:

Not classified Transport Hazard Class(es): Sub Risk: Not classified

Packing Group: Not classified

Environmental Hazards: Not environmentally hazardous for transport.

Special Precautions for user: None additional

Transport in bulk according to

Annex II of MARPOL73/78 and

the IBC Code:

Not Applicable

15. Regulatory Information

Safety, Health and Environmental Regulations Specific for the substance or mixture

Water Hazard Class (WGK)

Chemical Safety Assessment A Chemical Safety Assessment has not been carried out for this product.

16. Other Information

Concentration % Limits: EH A3=10.45% EH C3=33.33% SCI 2=79.69% SCI 3=4.38% EDI 2A=41.

37% SS 1=13.33%

Total Fractional Values: EH A3=9.57 EH C3=3.00 SCI 2=1.25 SCI 3=22.84 EDI 2A=2.42 SS 1=7.50

Further Information

Abbreviation	Meaning
Acute Tox. 3	Acute Toxicity – Oral Category 3
Acute Tox. 3	Acute Toxicity – Dermal Category 3
Acute Tox. 3	Acute Toxicity – Inhalation Category 3
Acute Tox. 4	Acute Toxicity – Oral Category 4
Acute Tox. 4	Acute Toxicity – Dermal Category 4
Acute Tox. 4	Acute Toxicity – Inhalation Category 4
Acute Tox. 5	Acute Toxicity – Oral Category 5
Acute Tox. 5	Acute Toxicity – Dermal Category 5
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Asp. Tox 1	Aspiration Hazard Category 1
Eye Dam. 1	Eye Damage / Irritation Category 1
Eye Irrit. 2A	Eye Damage / Irritation Category 2
Eye Irrit. 2B	Eye Damage / Irritation Category 2B
Flam. Liq. 3	Flammable Liquid, Hazard Category 3
Flam. Liq. 4	Flammable Liquid, Hazard Category 4
Flam. Sol. 2	Flammable Solid, Hazard Category 2
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H228	Flammable solid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child (exposure route).
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Phone: +61 8 8294 0451

ABN: 85 765 232 986

Email: admin@amcsupplies.com.au

Web: www.amcsupplies.com.au

H412	Harmful to aquatic life with long lasting effects.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames and hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe vapour or dust.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink, or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P301/330/331	If swallowed: rinse mouth. Do not induce vomiting.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with
	water/shower.
P304/340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for
	breathing.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to
	do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P311	Call a POISON CENTRE or doctor/physician.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P361	Remove/Take off immediately all contaminated clothing.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
STOT SE 3	Specific Target Organ Toxicity (Single Exposure) Category 3
Repr. 2	Toxic to Reproduction Category 2
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Irrit. 3	Skin Corrosion / Irritation Category 3
Skin Sens. 1A	Sensitization - Skin Category 1A
Skin Sens. 1B	Sensitization - Skin Category 1B
Skin Sens. 1B	Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate, but all data, instructions, and recommendations and/or suggestions are made without guarantee.

The Material Safety Data Sheet is intended to provide information for a health and safety assessment of the material. This document is not intended for quality assurance purposes.