

Safety Data Sheet Pina Colada Fragrance Revision 1, Date 22/09/2023

Phone: +61 8 8294 0451

Page 1 of 6

Email: admin@amcsupplies.com.au

Web: www.amcsupplies.com.au

Regulation 330 Schedule 7 as per Safe Work SA WHS Regulations

1. IDENTIFICATION

Product Name: Pina Colada Fragrance

Other Names:

Product Use Description: Fragrance for Consumer Product.

Contact Information: Organisation Local

 Organisation
 Location
 Telephone
 Ask For

 Adelaide Moulding and Candle Supplies
 7 Woodlands Terrace Edwardstown South Australia 5039
 08 8294 0451
 SDS Officer

 Poisons Information
 13 11 26

Centre

2. HAZARD IDENTIFICATION

Classification of Substance of Mixture:

Flammable Liquids (Category 4)
Skin Corrosion/Irritation (Category 3)
Skin-Sensitisation (Category 1)

Hazardous to the Aquatic Environment Acute (Category 1/2) Hazardous to the Aquatic Environment Chronic (Category 2)

H227 Combustible liquid. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Hazard Pictogram(s):



Signal Word: WARNING

Hazard Statements (s): H227 Combustible liquid.

 ${\sf H316\ Causes\ mild\ skin\ irritation}.$

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements(s): P210 Keep away from heat, sparks, open flames and hot surfaces – no smoking.

P261 Avoid breathing vapour or dust.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + 352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation persists: Get medical advice/attention.
P363 Wash contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use carbon dioxide, dry chemical, foam for extinction.

P391 Collect spillage.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to an approved waste disposal plant, in accordance with local

regulations.

Other Hazards: None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

EC No	No CAS No Description		GHS Classification	Concentration	
203-219-1	104-61-0	gamma-Nonalactone	Skin Irrit. 3;H316	20-<50%	
201-550-6	84-66-2	Diethyl phthalate Skin Irrit. 3-Aquatic Acute 3;H316- H402		20-<50%	
214-946-9	1222-05-5	1,3,4,6,7,8-Hexahydro- 4,6,6,7,8,8- hexamethylcyclopenta-gamma-2- benzopyran	Skin Irrit. 3-Aquatic Acute 1-Aquatic Chronic 1;H316-H410	10-<20%	
201-061-8	77-83-8	Ethyl methylphenylglycidate	Skin Sens. 1B-Aquatic Acute 2- Aquatic Chronic 2;H317-H411	10-<20%	
204-402-9	120-51-4	Benzyl benzoate	Acute Tox. 4-Acute Tox. 5-Aquatic Acute 1-Aquatic Chronic 2;H302-H313- H400-H411	10-<20%	
202-086-7	91-64-5	Coumarin	Acute Tox. 4-Skin Sens. 1B-Aquatic Acute 3;H302-H317-H402	5-<10%	
202-288-5	93-92-5	alpha-Methylbenzyl acetate	Flam. Liq. 4-Aquatic Acute 3;H227- H402	5-<10%	
227-813-5	5989-27-5	Limonene	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1BAsp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H226-H304-H315-H317- H410	1-<5%	
225-582-5	4940-11-8	Ethyl maltol	Acute Tox. 4;H302	1-<5%	
211-889-1	705-86-2	delta-Decalactone Flam. Liq. 4-Aquatic Acute 3;H227- H402		1-<5%	
204-464-7	121-32-4	Ethyl vanillin Acute Tox. 5-Eye Irrit. 2B-Aquatic Acute 3;H303-H320-H402		1-<5%	
213-192-8	928-96-1	cis-3-Hexenol Flam. Liq. 3-Eye Irrit. 2A;H226-H319		1-<5%	
203-306-4	105-54-4	Ethyl butyrate Flam. Liq. 3-Aquatic Acute 2;H226- H401		1-<5%	
204-881-4	128-37-0	Butylated hydroxytoluene Aquatic Acute 1-Aquatic Chronic 1;H410		1-<5%	
243-956-6	20665-85-4	Vanillin isobutyrate	Acute Tox. 5-Skin Irrit. 3;H303-H316	1-<5%	
204-642-4	123-68-2	Allyl hexanoate	Flam. Liq. 4-Acute Tox. 3-Acute Tox. 3- Acute Tox. 3-Aquatic Acute 1-Aquatic Chronic 3;H227-H301-H311-H331- H400- H412	0.1-<1%	
201-746-1	87-44-5	beta-Caryophyllene	Caryophyllene Skin Irrit. 3-Skin Sens. 1B-Asp. Tox 1; H304-H316-H317		
203-378-7	106-25-2	Acute Tox. 5-Skin Irrit. 2-Eye Dam. 1- Skin Sens. 1B-Aquatic Acute 2;H303-H315-H317-H318-H401		0.1-<1%	
204-262-9	118-58-1	Benzyl salicylate Acute Tox. 5-Eye Irrit. 2B-Skin Sens. 1B- Aquatic Acute 2-Aquatic Chronic 3;H303- H317-H320-H401-H412		0.1-<1%	
266-803-5	67634-00-8	Allyl (3-methylbutoxy)acetate Flam. Liq. 4-Acute Tox. 4-Skin Irrit. 2-Aquatic Acute 2;H227-H302-H315-H401		0.1-<1%	
220-292-5	2705-87-5	87-5 Allyl cyclohexanepropionate Acute Tox. 4-Acute Tox. 4-Skin Sens. 1-Aquatic Acute 1-Aquatic Chronic 1;H302-H312-H317-H332-H410		0.1-<1%	

209-578-0	586-62-9	Terpinolene	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 3- Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H227-H303-	0.1-<1%
			H304- H316-H317-H410	
201-291-9	80-56-8	alpha Pinene	Flam. Liq. 3-Acute Tox. 5-Skin Irrit. 2- Skin Sens. 1B-Asp. Tox 1-Aquatic Acute1-Aquatic Chronic 1;H226- H303-H304- H315-H317-H410	0.1-<1%
226-394-6	5392-40-5	Citral	Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2ASkin Sens. 1B-Aquatic Acute 2;H313- H315-H317-H319-H401	0.1-<1%
204-116-4	115-95-7	Linalyl acetate	Flam. Liq. 4-Skin Irrit. 2-Eye Irrit. 2AAquatic Acute 3;H227-H315-H319-H402	0.1-<1%
203-375-0	106-22-9	Citronellol	Acute Tox. 5-Acute Tox. 5-Skin Irrit. 2- Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 2;H303-H313-H315-H317-H319-H401	0.1-<1%
201-134-4	78-70-6	Linalool	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2- Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 3; H227-H303-H315-H317-H319-H402	0.1-<1%
203-118-2	103-50-4	Dibenzyl ether	Acute Tox. 5-Skin Irrit. 3-Skin Sens. 1B- Aquatic Acute 1-Aquatic Chronic 1;H303-H316-H317-H410	0.1-<1%
204-872-5	127-91-3	beta-Pinene	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1BAsp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H226-H304-H315-H317- H410	0.1-<1%

Substances with Community workplace exposure limits, not listed above:

EC	CAS	Name	%
204-881-4	128-37-0	Butylated hydroxytoluene	1.00%
201-550-6	84-66-2	Diethyl phthalate	29.06%

4. FIRST AID MEASURES

Skin Contact: IF ON SKIN, wash with plenty of soap and water.

Most important symptoms and Causes mild skin irritation.

Effects, both acute and delayed: May cause an allergic skin reaction.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Carbon dioxide, Dry chemical, Foam.

Hazardous Combustion Products: In case of fire, the following can release: Carbon monoxide, Unidentified organic compounds.

Special Protective Actions for

Fire Fighters:

in case of insufficient ventilation, wear suitable respiratory equipment.

6. ACCIDENTAL RELEASE MEASURES

Protective Equipment: Avoid inhalation.

Avoid contact with skin and eyes.

Adelaide Moulding and Candle Supplies 7 Woodlands Terrace Edwardstown SA 5039 ABN: 85 765 232 986 Personal Precautions: Remove all ignition sources and ventilate area.

Avoid contact with skin and inhalation of its vapours or smoke.

Emergency Procedures: No specific advice other than above.

Environmental Precautions: Keep contained to prevent contamination of drains, soil or ground water.

Should not be released into the environment.

To contain a spill: Dam up.

Methods and Suitable materials

Cover with an inert, inorganic, non-combustible absorbent material (e.g. dry-lime, sand, soda ash)

for spill containment: Dispose of according to local regulations. Avoid excessive inhalation of vapours.

7. HANDLING AND STORAGE

Precautions for safe handling: Use personal protective equipment as required. Keep away from heat, sparks, open flames and hot

surfaces. No smoking, Do not eat, drink or smoke when using this product.
Follow good manufacturing practices for housekeeping and personal hygiene.

Wash any exposed skin immediately after chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shouse should be thoroughly cleaned before reuse.

Measures to prevent fire: Keep away from heat, sparks, ignition sources and naked flames. No smoking.

Measures to protect the

environment:

Dispose of rinse water in accordance to local and national regulations.

Technical measures and storage

conditions:

Keep container closed when not in use.

Store in a cool, dry, ventilated area away from sources of heat, moisture, and incompatible substances. Protect container from physical damage. Ground/bond container and receiving

equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking

tools. Take precautionary measures against static discharge.

Specific end uses: Use in accordance with good manufacturing and industrial hygiene practices.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredient	CAS	EC	Description	Ppm	Mg/m3	Reference
Butylated	128-37-0	204-881-4	Long-term exposure	-	-	-
hydroxytoluene			limit (8-hour TWA			
			reference period)			
			Short-term exposure	-	-	-
			limit (15-minute			
			reference period)			
Diethyl	84-66-2	201-550-6	Long-term exposure	-	-	-
phthalate			limit (8-hour TWA			
			reference period)			
			Short-term exposure	-	-	-
			limit (15-minute			
			reference period)			

Exposure Controls

Eye Protection Avoid eye contact. Use safety glasses with side shield or goggles.

Use chemical safety goggles and/or a full-face shield where splashing is possible. Maintain eye wash

fountain and quick-drench facilities in work area.

Skin Protection Avoid skin contact. Wear protective gloves /face protection

Respiratory Protection Ensure adequate and ongoing ventilation is maintained in order to prevent build up of excessive

vapour and to ensure occupational exposure limits are adhered to.

If appropriate, and depending on your patterns and volumes of use, the following engineering

controls may be required as additional protective measures:

- a) Isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under negative air pressure relative to the rest of the plant.
- b) Employ the use of Personal protective equipment an approved, properly fitted respirator with organic vapour cartridges or canisters and particulate filters.
- c) Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures.
- d) Use closed systems for transferring and processing this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid

Aroma/Odour:

Relative density:

Flash Point (closed cup test):

pH:

Not determined

Initial boiling point/range:

Vapour pressure:

Not determined

Not determined

Not determined

Not determined

10. STABILITY AND REACTIVITY

Reactivity Hazards: No dangerous reaction known under conditions of normal use.

Chemical Stability: Stable under ordinary conditions of use and storage.

Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Conditions to Avoid: Avoid extreme heat.

Incompatibles: Avoid contact with strong acids, alkalis or oxidising agents.

Hazardous Decomposition

Products Stable under ordinary conditions of use and storage.

11. TOXICOLOGICAL INFORMATION

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in the UN GHS.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Assumed Toxicity Value (LD50 or ATE) for Acute Oral Toxicity: >5000 Assumed Toxicity Value (LD50 of ATE) for Acute Dermal Toxicity: >5000

Assumed Toxicity Value (LC50 or ATE) for Acute Inhalation Toxicity: Not Available

Inhalation Route: Not Available

Information about Hazardous Ingredients in the Mixture:

Ingredient	CAS	EC	LD50/ATE Oral	LD50/ATE	LC50/ATE	LC50 Route
				Dermal	Inhalation	
Coumarin	91-64-5	202-086-7	500	Not available	Not available	Not available
Benzyl benzoate	120-51-4	204-402-9	1500	4000	Noy available	Not available
Allyl hexanote	123-68-2	204-642-4	300	300	3	Vapour
Ethyl maltol	4940-11-8	225-582-5	1200	Not available	Not available	Not available

12. ECOLOGICAL INFORMATION

Toxicity: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects

Adelaide Moulding and Candle Supplies 7 Woodlands Terrace Edwardstown SA 5039 ABN: 85 765 232 986 Phone: +61 8 8294 0451 Email: admin@amcsupplies.com.au Web: www.amcsupplies.com.au Page 5 of 6 Persistence and degradability: Not Available

Bioaccumulative potential: Not Available

Mobility in soil: Not Available

PBT and vPvB Assessment: This substance does not meet the PBT/vPVB criteria of REACH, annex XIII

Other Adverse Effects: Not Available

13. DISPOSAL CONSIDERATIONS

Disposal: Dispose of according to local regulations. Avoid disposing into drainage systems and into the

environment. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. TRANSPORT INFORMATION

UN Number: UN3082

UN Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S

(1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran, Limonene)

Transport Hazard Class(es): 9
Sub Risk: Packing Group: III

Environmental Hazards: This is an environmentally hazardous substance.

Special Precautions for user: None additional Transport in bulk according to Not Applicable

Annex II of MARPOL73/78 and

the IBC Code:

15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations Specific for the substance or mixture

Water Hazard Class (WGK) 3

Chemical Safety Assessment A Chemical Safety Assessment has not been carried out for this product.

16. OTHER INFORMATION

Concentration % Limits: EH A2=11.76% EH A3=1.16% EH C2=12.25% EH C3=1.22% EH C4=53.72% SCI 3=7.95% SS 1=18.18%

Total Fractional Values: EH A1=1.14 EH A2=12.18 EH A3=123.28 EH C2=8.53 EH C3=85.34 EHC4=1.86 SCI 3=12.58 SS1=18.00

Key to revisions: Not applicable.

Further Information

Abbreviation	Meaning
Acute Tox. 4	Acute Toxicity – Oral Category 4
Acute Tox. 4	Acute Toxicity – Dermal Category 4
Acute Tox. 4	Acute Toxicity – Inhalation Category 4
Acute Tox. 5	Acute Toxicity – Oral Category 5
Acute Tox. 5	Acute Toxicity – Dermal Category 5
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Asp. Tox 1	Aspiration Hazard Category 1

Adelaide Moulding and Candle Supplies 7 Woodlands Terrace

Edwardstown SA 5039 ABN: 85 765 232 986 Phone: +61 8 8294 0451 Email: admin@amcsupplies.com.au Web: www.amcsupplies.com.au Page 6 of 6

Eye Dam. 1	Eye Damage / Irritation Category 1
Eye Irrit. 2A	Eye Damage / Irritation Category 2
Eye Irrit. 2B	Eye Damage / Irritation Category 2B
Flam. Lig. 3	Flammable Liquid, Hazard Category 3
Flam. Liq. 4	Flammable Liquid, Hazard Category 4
Flam. Sol. 2	Flammable Solid, Hazard Category 2
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H228	Flammable solid.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harming in contact with skin.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
P210	Keep away from heat, sparks, open flames and hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink, or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with
	water/shower.
P304/340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for
	breathing.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
2010	and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.

P391	Collect spillage.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Irrit. 3	Skin Corrosion / Irritation Category 3
Skin Sens. 1	Sensitization - Skin Category 1
Skin Sens. 1B	Sensitization - Skin Category 1B

Further information

The information in this safety data sheet is to the best of our knowledge true and accurate, but all data, instructions, and recommendations and/or suggestions are made without guarantee.

The Material Safety Data Sheet is intended to provide information for a health and safety assessment of the material. This document is not intended for quality assurance purposes.